

NEW AUDIO



OK

系列  
series



全新的OK系列KTV包房音箱，高声压及良好的低频控制力和下潜量，声音更感厚实，精致紧凑的外观有黑色与白色选择，更容易与装修环境搭配，OK系列是能胜任KTV包房、量版的音箱。

New OK KTV speaker series, high pressure and control of low frequency and amount of diving, sound more thick, exquisite compact appearance has black and white choice, easier to decorate the environment collocation, OK series is qualified for KTV rooms, version of the speaker.

## OK-210



### 结构特性:

号角高音搭配双10寸低音的OK-210拥有外观新颖高频亮丽低频柔和而醇厚的特点, 多种吊挂方式使安装与使用极其方便, 有黑色、白色供选择, 特别适用于商务KTV包房及量贩KTV房。

### 电性能参数 Electrical performance parameter

频响范围(±10dB) Frequency response (±10dB)	40Hz - 20KHz
声压灵敏度(1瓦,1米) Pressure sensitivity(1 watt.1 m)	95 dB SPL
最大连续声压级 Maximum continuous sound pressure level	120 dB SPL
峰值声压值 Peak sound pressure level	123 dB SPL
输入阻抗 Input impedance	4 ohm
额定输出功率 Rated output power	350 W
峰值输出功率 Peak output power	700 W
低频 Woofer	2x 10 英寸精密低频换能器 2x 10 inch precision woofer transducer
高频 High Frequency Driver	1x 1.4 英寸精密高频驱动器 1x 1.4 inch precision high frequency driver
低频 Woofer Size	50mm
高频 High Frequency Driver Size	36mm

### Structural Features:

Horn tweeters collocation dual 10-inch bass, OK-210 has the characteristics of high frequency

beautiful appearance novel low-frequency soft and mellow, a variety of hanging way make the installation and use of extremely convenient,

### 结构和特性 Structure and characteristics

箱体 BOX	内部加固的18 mm 厚桦木多层板 Interior reinforced 18 mm thick birch plywood
连接器 Connectors	2只4 针PA-COM插座 2Pcs 4-hole PA-COM plugs
箱体表面处理 Cabinet surface	标准色为 黑色, 专业环保点状漆覆盖 standard colour is black, professional no environment pollution paint covers
保护格栅 Protective grille	1.2mm厚的透声孔钢板 1.2mm Thick sound-transparent holes steel plate
体积 (宽x深x高) Dimensions (WxDxH)	603mm x 400mm x 378mm
重量 weight	19 公斤 19 kg



there are black and white for choice, especially suitable for business KTV rooms and KTV room.





# OK-10B



## 电性能参数 Electrical performance parameter

频响范围(±10dB) Frequency response (±10dB)	48Hz - 20KHz
声压灵敏度(1瓦.1米) Pressure sensitivity(1 watt.1 m)	93 dB SPL
最大连续声压级 Maximum continuous sound pressure level	113 dB SPL
峰值声压值 Peak sound pressure level	116 dB SPL
输入阻抗 Input impedance	8 ohm
额定输出功率 Rated output power	150 W
峰值输出功率 Peak output power	300 W
低频 Woofer	1x 10 英寸精密低频换能器 1x 10 inch precision woofer transducer
高频 High Frequency Driver	2x 3 英寸精密高频驱动器 2x 3 inch precision high frequency driver
低频 Woofer Size	50mm
高频 High Frequency Driver Size	14mm

## 结构和特性 Structure and characteristics

箱体 BOX	内部加强的15 mm 厚环保中密度纤维板 Interior reinforced 15 mm thick no environment pollution MDF wooden
连接器 Connectors	接线柱 binding post
箱体表面处理 Cabinet surface	标准色为 黑色, 专业环保点状漆覆盖 standard colour is black, professional no environment pollution paint covers
保护格栅 Protective grille	1.2mm厚的透声孔钢板 1.2mm Thick sound-transparent holes steel plate
体积 (宽x深x高) Dimensions (WxDxH)	520mm x 300mm x 315mm
重量 weight	12 公斤 12 kg



### 结构特性:

采用二分频三单元（一低音二高音）设计的OK-10B, 话筒演唱轻松, 中高频细腻, 低频丰厚, 外形大方, 特别适用于量贩KTV房。

### Structural Features:

The three ways frequency five unit design of OK - 10 B, singing

easy, high frequency in the delicate, rich and low frequency, generous appearance, especially suitable for KTV room.

